



## Telehandler / Zoom Boom

Used Telehandler Concord - Telehandlers have numerous names including a teleporter, Cherry picker, telescopic handler or boom lift. These machines are utilized in agriculture and many different industries. This machine functions similarly to a crane and a forklift with the ability to extend upward and forward. Numerous attachments can be placed at the end of the articulating boom to conduct a variety of different jobs. Common attachments include pallet forks, a winch, a bucket or a muck grab. The main telehandler attachment is the pallet forks. Pallet forks enable the operator to move loads to and from a variety of locations that would otherwise be considered unreachable with a standard forklift. Telehandlers allow cargo pallets to be loaded and unloaded from a trailer and placed on high locations such as racking or rooftops. Often, high rooftop locations would need a crane although, telehandlers can accomplish these tasks much more efficiently. It can be expensive and impractical to rely on a crane or expansive industrial equipment to finish particular tasks. Within agriculture, the bucket or bucket grab is among the most popular attachments. Moving items from unreachable locations that cannot be completed with a backhoe loader or wheeled loader give telehandlers a huge advantage. For instance, these industrial machines can directly access a hopper or trailer with high sides; applications that would otherwise rely on a conveyor, loading ramp or similar equipment. Relying on one piece of equipment to complete a variety of jobs saves time, money and storage. Telehandler machines can work in conjunction with a crane jib. Various attachments may be used including rotators, dirt buckets, grain buckets and power booms. Agricultural models can be outfitted with power take-off and 3-point linkage, making the telehandler and exceptionally useful. However, the main advantage of the telehandler is additionally its' largest limitation. When raising or extending with heavy loads, the boom functions similar to a lever. Despite significant counterweights in the rear, the telehandler can be subject to instability at times, decreasing the lifting capacity as the working radius or distance between the center of the load and the front of the wheels increases. When a telehandler functions as a single boom loader (as opposed to twin arms) and carrying a heavy load, there can be a potential for weakness even in the best designs. A machine with a 5K lb. capacity could safely lift 400 lbs. while fully extended using a retracted low boom angle. The same piece of equipment with a five thousand pound lift capacity and retracted boom may be capable as supporting up to ten thousand pounds once the boom is raised to seventy degrees. Monitoring the angle, weight and boom height, there are load charts on this equipment to outline which tasks can be safely conducted. Newer telehandler models rely on computers and sensors to monitor the machine. The operator cannot continue once the machine's limits have been reached. They are warned and cut off from accessing the control input. There are front stabilizers that can drastically enhance the machine's lifting capacity while it is stationary. A stabilizing rotary joint between the upper and lower frames may be called a mobile crane that can use a bucket. There are compact telehandler models that differ in boom design, size, reach and weight. Telehandlers fall into the compact category if the unit weighs in at 11,000 lbs. or less. Compact units have a two-stage boom compared to larger machines that feature three or four boom designs. Compact models rely on a low pivot boom to facilitate better cab visibility as the operator transports loads. There are narrower and smaller dimensions offered with the compact telehandler. Compact telehandlers have a reach capacity ranging between 13 to 20 feet with a lift capacity ranging from 5k to 7k pounds. The versatility of the compact telehandler makes it popular in a variety of applications. This machine can be utilized for carrying tools or as a pick and place unit. Compact units are ideal for cramped locations. Residential applications are common as contractors relish their useful nature with framing applications and where height restrictions come into play. These machines can facilitate internal building access. Compact telehandlers are used in many applications including nurseries, erecting steel, multi-story construction, masonry, strip malls, garages and similar jobs. Agri-business and farming applications rely on telehandlers for a variety of jobs. Telehandlers are made with two or four-wheel drive as well as crab steering. The unit can travel over longer

ranges at higher speeds with two-wheel drive, making it ideal for moving throughout job sites. Four-wheel drive units can travel over harder terrain while offering a tighter turning radius. Crab steering increases overall maneuvering and enables the front and back wheels to move 45 degrees to the left or the right. There are a variety of cab interior options available for compact telehandlers. There is a rollover protective cage to enhance safety on less expensive models. Higher models come with a heater, a completely enclosed cab, defroster and windshield wiper. Operators enjoy spacious accommodation for ultimate comfort. Additional features such as cup holders, air conditioning, tilt steering, suspension seats and satellite radio are all options. Many high-pressure hydraulics and high-flow auxiliary hydraulics operate the numerous attachments. The different attachments allow the machine to be capable of many options. All of these attachments enable the machine to conduct a variety of jobs. Compact machines conduct ground-engaging jobs. It is simple to transform a compact telehandler into a mini excavator with a bucket attachment. Light and heavy-duty buckets can be used to move items, augers can plant trees or drill holes, rotating and side-shifting fork carriages facilitate pick-and-place, truss booms are in place for extending reach, sweeping brooms and crane hooks are other popular attachments. Skid steer attachments are being made for versatility and other compact telehandler designs.